

MATERIAL SAFETY DATA SHEET

Product Name: Tar & Bitumen Remover

Page: 1 of 5

This revision issued: July, 2006

Section 1 - Identification of Chemical Product and Company

Premier One Products Pty Ltd
Unit 10 11-13 Potter Close
Wetherill Park, NSW 2164

Phone: 02 9756 2419

Fax: 02 756 2020

Email: sales@premieroneproducts.com.au

Substance: Surfactant blend in liquid hydrocarbon solution.
Trade Name: Tar & Bitumen Remover
Product Use: Tar Degreasing solvent.
Creation Date: July, 2005
Revision Date: July, 2006

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of NOHSC Australia.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

Risk Phrases: R10, R22, R38, R65. Flammable. Harmful if swallowed. Irritating to skin. Harmful: May cause lung damage if swallowed.

Safety Phrases: S16, S20, S46, S24/25, S36/37. Keep away from sources of ignition - No smoking. When using, do not eat or drink. If swallowed, contact a doctor or Poisons Information Centre immediately and show this container or label. Avoid contact with skin and eyes. Wear suitable protective clothing and gloves.

SUSDP Classification: S5

ADG Classification: Class 3 (TURPENTINE SUBSTITUTE)

UN Number: 1300

Emergency Overview

Physical Description & Colour: YELLOW liquid.

Odour: Characteristic odour.

Major Health Hazards: harmful if swallowed, skin irritant, if aspirated, may cause lung damage.

Potential Health Effects

Inhalation

Short Term Exposure: Significant inhalation exposure is considered to be unlikely. Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: Exposure via eyes is considered to be unlikely. This product may be irritating to eyes, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. This product is unlikely to cause any irritation problems in the short or long term.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:**NOHSC:** No significant ingredient is classified as carcinogenic by NOHSC.**NTP:** No significant ingredient is classified as carcinogenic by NTP.**IARC:** No significant ingredient is classified as carcinogenic by IARC.**Section 3 - Composition/Information on Ingredients**

Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
Solvent naphtha (petroleum), light arom.	64742-95-6	<60	not set	not set
Medium aliphatic petroleum solvent	64742-88-7	<60	not set	not set
Other non hazardous ingredients		to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures**General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

Inhalation: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Skin Contact: Quickly and gently blot away excess liquid. Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: Quickly and gently blot material from eyes. No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed. Obtain medical advice if irritation becomes painful or lasts more than a few minutes.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: This product is classified as flammable. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Preferred extinguishing media are carbon dioxide, dry chemical, foam. Foam is the preferred medium for large fires. Ensure that no spillage enters drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade.

Flash point: 36°C, approx

Upper Flammability Limit: No data.

Lower Flammability Limit: No data.

Autoignition temperature: No data.

Flammability Class: Flammable

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise as a minimum, protective glasses and, preferably, goggles. If there is

MATERIAL SAFETY DATA SHEET

a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a type A cartridge, suitable for organic vapours.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 1000L of flammable liquids of Packaging Group III, you are probably required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

Exposure Limits

TWA (mg/m³)

STEL (mg/m³)

Exposure limits have not been established by NOHSC for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that vapours and mists are minimised.

Eye Protection: Eye protection such as protective glasses or goggles is recommended when this product is being used.

Skin Protection: Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should, if practical, be provided near to where this product is being used.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Green liquid.
Odour:	Characteristic odour.
Boiling Point:	>149°C at 100kPa
Freezing/Melting Point:	No specific data. Liquid at normal temperatures.
Volatiles:	No specific data. Expected to be low at 100°C.
Vapour Pressure:	<3.3 kPa at 20°C
Vapour Density:	No data.
Specific Gravity:	0.86
Water Solubility:	Insoluble.
pH:	No data.
Volatility:	No data.

MATERIAL SAFETY DATA SHEET

Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water Distribution:	No data
Autoignition temp:	No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

Incompatibilities: oxidising agents.

Fire Decomposition: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Local Effects:

Target Organs: eyes, skin

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Solvent Naphtha (petroleum), Light Arom.	Conc>=10%: T; R45 *; R65
Medium aliphatic petroleum solvent	Conc>=10%: Xn; R65
Note P reveals that this designation (May Cause Cancer) is not necessary if the benzene content of the ingredient is below 0.1% which we believe is the case.	

Section 12 - Ecological Information

Insufficient data to be sure of status.

Section 13 - Disposal Considerations

Disposal: Containers should be emptied as completely as practical before disposal. If possible, recycle containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. Please do NOT dispose into sewers or waterways.

Section 14 - Transport Information

ADG Code: 1300, TURPENTINE SUBSTITUTE

Hazchem Code: 3[Y]

Special Provisions: SP184

Dangerous Goods Class: Class 3, Flammable liquids.

Packaging Group: III

Packaging Method: 3.8.3

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, except where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are to be found in the public AICS Database.

The following ingredients: Solvent naphtha (petroleum), light arom., Medium aliphatic petroleum solvent (both Liquid Hydrocarbons), are mentioned in the SUSDP.

MATERIAL SAFETY DATA SHEET

Section 16 - Other Information

This MSDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail
AICS	Australian Inventory of Chemical Substances
CAS Number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOHSC	National Occupational Health and Safety Commission
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSDP	Standard for the Uniform Scheduling of Drugs & Poisons
UN Number	United Nations Number

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the NOHSC document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]

Copyright © Kilford & Kilford Pty Ltd, July, 2006.

<http://www.kilford.com.au/> Phone (02)9251 4532